

Hauptsitz

Gloor Pumpenbau AG
Thunstrasse 25
CH-3113 Rubigen
Tel. +41 (0)58 255 43 34
info@gloor-pumpen.ch
www.gloor-pumpen.ch

Filiale Mittelland

Gloor Pumpenbau AG
Industriestrasse 25
CH-5036 Oberentfelden

Filiale Suisse Romande

Gloor Pumpenbau SA
Rue du Collège 3 | Case postale
CH-1410 Thierrens
Tél. +41 (0)58 255 43 34
info@gloor-pompes.ch
www.gloor-pompes.ch

GHV Series

Variable speed sets equipped with Hydrovar® frequency converter and 2-3-4 multistage vertical pumps.

Specifications

Number of pumps: 1 to 4
Delivery: up to 640 m³/h
Head: up to 160 m
Input voltage of panel
3 x 400 V 50 Hz (three-phase)
Power range: 4 x 37 kW (three-phase)
Motor starting via variable frequency operation
Water temperature of the liquid: 0°C to +80°C
Pump type: vertical

Materials

Pump: Stainless steel
Manifold: AISI 304 stainless steel

Product applications and characteristics

Easy to install

Trouble-free servicing

Pressure transducer controlled

Compact solution

Constant output pressure

Variable speed motors with consequently reduced noise

Protection against dry running

Accessories: Membrane vessel

Versions with non-return valve on suction line available on request

Special configurations available on request



For a complete list of technical information, consult www.lowara.com