

#### Hauptsitz

Gloor Pumpenbau AG  
Thunstrasse 25  
CH-3113 Rubigen  
**Tel. +41 (0)58 255 43 34**  
**info@gloor-pumpen.ch**  
**www.gloor-pumpen.ch**

#### Filiale Mittelland

Gloor Pumpenbau AG  
Industriestrasse 25  
CH-5036 Oberentfelden

#### Filiale Suisse Romande

Gloor Pumpenbau SA  
Rue du Collège 3 | Case postale  
CH-1410 Thierrens  
**Tél. +41 (0)58 255 43 34**  
**info@gloor-pompes.ch**  
**www.gloor-pompes.ch**

# GHV Series

Variable speed sets equipped with Hydrovar® frequency converter and two multistage vertical pumps.

## Specifications

Number of pumps: from 2  
Delivery: up to 28 m<sup>3</sup>/h  
Head: up to 160 m  
Input voltage of panel:  
1 x 230 V 50 Hz (single-phase)  
3 x 400 V 50 Hz (three-phase)  
Power range:  
2 x 2,2 kW (single-phase)  
2 x 4 kW (three-phase)  
Motor starting via variable frequency operation  
Water temperature of the liquid: 0°C to +80°C  
Pump type: vertical e-SV™ series

## Materials

Pump: Stainless steel  
Manifold: AISI 304 stainless steel

## Product applications and characteristics

Easy to install

---

Trouble-free servicing

---

Pressure transducer controlled

---

Compact solution

---

Constant output pressure

Variable speed motors with consequently reduced noise

---

Protection against dry running

---

Accessories: Hydro tube

---

Versions with non-return valve on suction line available on request

---

For hydraulic performances of 3 and 4 pumps boosters please check our technical catalogue

---

Special configurations available on request

